

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name**

KABRIC Floor

**Product no.**

Woca - Kabric Floor

**REACH registration number**

Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Paint

**Uses advised against**

-

The full text of any mentioned and identified use categories are given in section 16

### 1.3. Details of the supplier of the safety data sheet

**Company and address**

Flügger Denmark A/S  
Islevdalvej 151  
DK-2610 Rødovre  
Tlf. +45 70 15 15 05  
www.detalecph.com

**Contact person****E-mail**

hello@detalecph.com

**SDS date**

2021-02-25

**SDS Version**

1.0

### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

### 2.2. Label elements

**Hazard pictogram(s)**

Not applicable

**Signal word**

-

**Hazard statement(s)**

Not applicable

**Precautionary statements**

General	-
Prevention	-
Response	-
Storage	-
Disposal	-

**Identity of the substances primarily responsible for the major health hazards**

Not applicable

### Additional labelling

Contains 2-Methyl-2H-isothiazol-3-one (MIT), 5-Chloro-2-methyl-4-isothiazolin-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1)). May produce an allergic reaction. (EUH208).  
Safety data sheet available on request. (EUH210)

### Unique formula identifier (UFI)

-

### 2.3. Other hazards

Not applicable

### Additional warnings

Not applicable

### VOC (volatile organic compound)

VOC-Max: 115 g/l, MAXIMUM VOC CONTENT (A/d (WB)): 130 g/l.

## SECTION 3: Composition/information on ingredients

### 3.1/3.2. Substances/Mixtures

NAME:	(2-methoxymethylethoxy)propanol
IDENTIFICATION NOS.:	CAS-no: 34590-94-8 EC-no: 252-104-2 REACH-no: 01-2119450011-60
CONTENT:	2.5 - <5%
CLP CLASSIFICATION:	NA
NOTE:	O L

NAME:	2-Methyl-2H-isothiazol-3-one (MIT)
IDENTIFICATION NOS.:	CAS-no: 2682-20-4 EC-no: 220-239-6
CONTENT:	<0.0015%
CLP CLASSIFICATION:	Acute Tox. 3, Acute Tox. 3, Skin Corr. 1B, Skin Sens. 1A, Eye Dam. 1, Acute Tox. 2, STOT SE 3, Aquatic Acute 1, Aquatic Chronic 1 H301, H311, H314, H317, H318, H330, H335, H400, H410 (M-acute = 10) (M-chronic = 1)

NAME:	5-Chloro-2-methyl-4-isothiazolin-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))
IDENTIFICATION NOS.:	CAS-no: 55965-84-9 EC-no: - Index-no: 613-167-00-5
CONTENT:	<0.0015%
CLP CLASSIFICATION:	Acute Tox. 3, Acute Tox. 2, Skin Corr. 1C, Skin Sens. 1A, Eye Dam. 1, Acute Tox. 2, Aquatic Acute 1, Aquatic Chronic 1 H301, H310, H314, H317, H318, H330, H400, H410 (M-acute = 100) (M-chronic = 100)

(\*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.  
O = Organic solvent L = European occupational exposure limit.

### Other information

ATEmix(inhale, dust/mist) > 5  
ATEmix(dermal) > 2000  
ATEmix(oral) > 2000

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Bring the person into fresh air and stay with him/her.

#### Skin contact

Immediately remove contaminated clothing and shoes. Ensure that skin, which has been exposed to the material, is washed thoroughly with soap and water. Skin cleanser can be used. DO NOT use solvents or thinners.

#### Eye contact

Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting,

unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

#### **Burns**

Not applicable

#### **4.2. Most important symptoms and effects, both acute and delayed**

This product contains substances that may trigger an allergic reaction to predisposed persons.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Nothing special

#### **Information to medics**

Bring this safety data sheet.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

#### **5.2. Special hazards arising from the substance or mixture**

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

No specific requirements.

#### **6.2. Environmental precautions**

No specific requirements.

#### **6.3. Methods and material for containment and cleaning up**

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

#### **6.4. Reference to other sections**

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

See section on 'Exposure controls/personal protection' for information on personal protection.

#### **7.2. Conditions for safe storage, including any incompatibilities**

Always store in containers of the same material as the original container.

#### **Storage temperature**

Store frost-free.

#### **7.3. Specific end use(s)**

This product should only be used for applications quoted in section 1.2

### **SECTION 8: Exposure controls/personal protection**

#### **8.1. Control parameters**

##### **OEL**

(2-methoxymethylethoxy)propanol

Long-term exposure limit (8-hour TWA reference period): 50 ppm | 308 mg/m<sup>3</sup>

Short-term exposure limit (15-minute reference period): - ppm | - mg/m<sup>3</sup>

Comments: Sk (Sk = Can be absorbed through skin.)

##### **DNEL / PNEC**

According to EC-Regulation 2015/830

DNEL ((2-methoxymethylethoxy)propanol): 308 mg/m<sup>3</sup>  
 Exposure: Inhalation  
 Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 283 mg/kg bw/day  
 Exposure: Dermal  
 Duration of Exposure: Long term – Systemic effects - Workers

DNEL ((2-methoxymethylethoxy)propanol): 37,2 mg/m<sup>3</sup>  
 Exposure: Inhalation  
 Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 121 mg/kg bw/day  
 Exposure: Dermal  
 Duration of Exposure: Long term – Systemic effects - General population

DNEL ((2-methoxymethylethoxy)propanol): 36 mg/kg bw/day  
 Exposure: Oral  
 Duration of Exposure: Long term – Systemic effects - General population

PNEC ((2-methoxymethylethoxy)propanol): 19 mg/l  
 Exposure: Freshwater

PNEC ((2-methoxymethylethoxy)propanol): 1,9 mg/l  
 Exposure: Marine water

PNEC ((2-methoxymethylethoxy)propanol): 4168 mg/l  
 Exposure: Sewage Treatment Plant

PNEC ((2-methoxymethylethoxy)propanol): 70,2 mg/kg dw  
 Exposure: Freshwater sediment

PNEC ((2-methoxymethylethoxy)propanol): 7,02 mg/kg dw  
 Exposure: Marine water sediment

PNEC ((2-methoxymethylethoxy)propanol): 2,74 mg/kg dw  
 Exposure: Soil

## 8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, eating and drinking are not allowed in the work premises

### Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

### Measures to avoid environmental exposure

No specific requirements.

### Individual protection measures, such as personal protective equipment



### Generally

Use only CE marked protective equipment.

### Respiratory Equipment

Use full-face mask (EN 136) with combination filter (A2P2, EN 14387) when spraying.

Dust, which is unhealthy, is produced when treated surfaces are grinded. Use respiratory protection if necessary (P2, EN 143).

### Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester. Chemical resistant suit with helmet/hood (Type 4, 5, 6 Category III) is recommended for spray applications.

### Hand protection

Recommended: Nitrile rubber (EN 374)  
Breakthrough time: See the manufacturer's instructions.

### Eye protection

Wear safety glasses with side shields.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Form	Liquid
Colour	Whitish
Odour	Characteristic
Odour threshold (ppm)	No data available.
pH	8,5
Viscosity (40°C)	No data available.
Density (g/cm <sup>3</sup> )	1,3-1,4

### Phase changes

Melting point (°C)	No data available.
Boiling point (°C)	No data available.
Vapour pressure	No data available.
Decomposition temperature (°C)	No data available.
Evaporation rate (n-butylacetate = 100)	No data available.

### Data on fire and explosion hazards

Flash point (°C)	No data available.
Ignition (°C)	No data available.
Auto flammability (°C)	No data available.
Explosion limits (% v/v)	No data available.
Explosive properties	No data available.

### Solubility

Solubility in water	Soluble
n-octanol/water coefficient	No data available.

### 9.2. Other information

Solubility in fat (g/L)	No data available.
-------------------------	--------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

### 10.3. Possibility of hazardous reactions

Nothing special

### 10.4. Conditions to avoid

Nothing special

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity

Substance: 2-Methyl-2H-isothiazol-3-one (MIT)  
Species: Rat

Test: LC50  
Route of exposure: Inhalation, dust/mist, 4 h  
Result: 0,53 mg/l

**Skin corrosion/irritation**

No data available.

**Serious eye damage/irritation**

No data available.

**Respiratory or skin sensitisation**

This product contains substances that may trigger an allergic reaction to predisposed persons.

**Germ cell mutagenicity**

No data available.

**Carcinogenicity**

No data available.

**Reproductive toxicity**

No data available.

**STOT-single exposure**

No data available.

**STOT-repeated exposure**

No data available.

**Aspiration hazard**

No data available.

**Long term effects**

Nothing special

## SECTION 12: Ecological information

### 12.1. Toxicity

Substance: 5-Chloro-2-methyl-4-isothiazolin-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: *Oncorhynchus mykiss*

Test: NOEC

Duration: 14 d

Result: 0,05 mg/l

Substance: 5-Chloro-2-methyl-4-isothiazolin-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: *Oncorhynchus mykiss*

Test: LC50

Duration: 96 h

Result: 0,19 mg/l

Substance: 5-Chloro-2-methyl-4-isothiazolin-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: *Daphnia magna*

Test: EC50

Duration: 48 h

Result: 0,1 mg/l

Substance: 5-Chloro-2-methyl-4-isothiazolin-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: *Skeletonema costatum*

Test: EC50

Duration: 48 h

Result: 0,0052 mg/l

Substance: 5-Chloro-2-methyl-4-isothiazolin-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: *Skeletonema costatum*

Test: NOEC

Duration: 48 h

Result: 0,00049 mg/l

Substance: 5-Chloro-2-methyl-4-isothiazolin-3-one/2-Methyl-2H-isothiazol-3-one (3:1) (CMIT/MIT (3:1))

Species: *Daphnia magna*

Test: NOEC

Duration: 21 d

Result: 0,004 mg/l

Substance: 2-Methyl-2H-isothiazol-3-one (MIT)

Species: *Daphnia magna*

Test: LC50

Duration: 48 h

Result: 0,93-1,9 mg/l

Substance: 2-Methyl-2H-isothiazol-3-one (MIT)

According to EC-Regulation 2015/830

Species: Selenastrum capricornutum  
 Test: EC50  
 Duration: 72 h  
 Result: 0,158 mg/l

Substance: 2-Methyl-2H-isothiazol-3-one (MIT)  
 Species: Daphnia magna  
 Test: NOEC  
 Duration: 21 d  
 Result: 0,04 mg/l

## 12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
2-Methyl-2H-isothiazol-3-one (... (2-methoxymethylethoxy)propano...	Yes Yes	Simulation study Manometric Respirometry Test	98 % >60%

## 12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BCF
5-Chloro-2-methyl-4-isothiazol...	No	0,401	No data available
2-Methyl-2H-isothiazol-3-one (... (2-methoxymethylethoxy)propano...	No No	-0,75 0,0043	No data available No data available

## 12.4. Mobility in soil

5-Chloro-2-methyl-4-isothiazol...: Log Koc= 0,3959519, Calculated from LogPow (High mobility potential.).  
 2-Methyl-2H-isothiazol-3-one (...: Log Koc= -0,515525, Calculated from LogPow (High mobility potential.).  
 (2-methoxymethylethoxy)propano...: Log Koc= 0,08180517, Calculated from LogPow (High mobility potential.).

## 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

## 12.6. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.  
 This product contains substances, which may cause adverse long-term effects to the aquatic environment.

# SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

### Waste

EWC code

08 01 12

waste paint and varnish other than those mentioned in 08 01 11

### Specific labelling

Not applicable

### Contaminated packing

No specific requirements.

# SECTION 14: Transport information

## 14.1 – 14.4

Not dangerous goods according to ADR, IATA and IMDG.

### ADR/RID

14.1. UN number	-
14.2. UN proper shipping name	-
14.3. Transport hazard class(es)	-
14.4. Packing group	-
Notes	-
Tunnel restriction code	-

### IMDG

UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-

EmS	-
MP**	-
Hazardous constituent	-
<b>IATA/ICAO</b>	
UN-no.	-
Proper Shipping Name	-
Class	-
PG*	-

#### 14.5. Environmental hazards

-

#### 14.6. Special precautions for user

-

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

(\*) Packing group

(\*\*) Marine pollutant

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Restrictions for application

People under the age of 18 shall not be exposed to this product cf. Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

##### Demands for specific education

-

##### Additional information

Not applicable

##### Seveso

-

##### Biocidal reg. no.

Not applicable

##### Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding.

Council Directive 94/33/EC of 22 June 1994 on the protection of young people at work.

Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office, 2002.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP).

Regulation (EC) 1907/2006 (REACH).

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

H301 - Toxic if swallowed.

H310 - Fatal in contact with skin.

H311 - Toxic in contact with skin.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.



- H318 - Causes serious eye damage.
- H330 - Fatal if inhaled.
- H335 - May cause respiratory irritation.
- H400 - Very toxic to aquatic life.
- H410 - Very toxic to aquatic life with long lasting effects.

**The full text of identified uses as mentioned in section 1**

-

**Additional label elements**

Not applicable

**Other**

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.  
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.  
A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

**The safety data sheet is validated by**

STTAN

**Date of last essential change  
(First cipher in SDS version)**

-

**Date of last minor change  
(Last cipher in SDS version)**

-